This Page Is Inserted by IFW Operations and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problems Mailbox.

THIS PAGE BLANK (USPTO)


PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 5:		(11) International Publication Number:	WO 94/03855
G06F 9/46		(43) International Publication Date: 17 Febr	uary 1994 (17.02.94)
(21) International Application Number: PCT/F1 (22) International Filing Date: 28 July 1993 (30) Priority data: 923430 29 July 1992 (29.07.92)	(28.07.9	CZ. DE. DK. ES. FI. GB. HU. IP	, KP, KR, KZ, LK, , PL, PT, RO, RU, an patent (AT, BE, , IT, LU, MC, NI
(71) Applicant (for all designated States except US): NO LECOMMUNICATIONS OY [FI/FI]; Mākky totie 1, FIN-02600 Espoo (FI).	KIA T /län pui	Published S- With international search report.	
72) Inventor; and 75) Inventor/Applicant <i>(for US only) :</i> SYVÄNIEM [FI/FI]; Nissnikuntie 1 B 8, FIN-02430 Masala	I, Mari a (FI).	ti	
74) Agent: OY KOLSTER AB; Iso Roobertinkatu 00121 Helsinki (FI).	23, FIN		
·			



(57) Abstract

The invention relates to a method for managing resources allocated in a computer, wherein the allocated resources are maintained or released by time monitoring. In the invention, a task controller (1) is allocated for the management of resources required for a task to be executed; the controller (1) allocates resources (3, 4) required to execute the task; the controller starts time monitoring in each resource; if required by the task, the controller renews the resource allocations before the expiry of the respective time monitoring periods; and the controller (1) releases all resources allocated for the task after the completion of the task.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	MR	Mauritania
		GA	Gabon	MW	Malawi
AU	Australia			NE	Niger
88	Barbados	GB.	United Kingdom		Netherlands
BE	Belgium	GN	Guinea	NL	
BF	Burkina Faso	GR	Greuce	NO	Norway
BG	Bulgaria	HU	Hungari	NZ	New Zealand
BJ.	Benin	ΙE	Irelai.	PL.	Poland
		ίŦ	Itals	PT	Portugai
BR	Brazil	JP	Japan	RO	Romania
BY	Belarus	KP	De: tic People's Republic	RÜ	Russian Federation
CA	Canada	a.r		SD	Sudan
CF	Central African Republic		of Keria		
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	K2	Kazakhstan	SI	Slovenia
		LI	Liechtenstein	SK	Slovak Republic
CI	Côte d'Ivoire	LK	Sri Lanta	SN	Senegal
CM	Cameroon			TD	Chad
CN	China	LU	Luxembourg	ŤĠ	Togo
cs	Czechoslovakia	LV	Latvia		
cz	Czech Republic	MC	Monaco	UA	Ukraine
		MG	Madagascar	US	United States of America
DE	Germany	ML	Mali	UZ	Lizbekistan
DK	Denmark			VN	Vict Nam
ES	Spein	MN	Mongolia	***	
P۱	Finland		•		

PCT/FI93/00304

5

10

15

20

25

30

35

Method for managing resources allocated in a computer

This invention relates to a method for managing resources allocated in a computer, wherein the allocated resources are maintained or released by time monitoring.

The execution of a specific task in a computer system often requires co-operation between several resources based on recurrent use of the hardware, software and/or memory resources. The use of resources thus refers to the allocation of the parts of the computer system for the execution of a specific task, no matter whether these parts belong to the hardware, computation or memory capacity of the computer.

The resource allocation system has been problematic in that the known computers do not comprise any particularly advanced systems for monitoring allocated resources. Especially after the completion of the task assigned to the computer, the release of all or some of the resources may fail for some reason, e.g. due to malfunction, a programming error, etc. In practice, this problem easily results in that the system runs short of certain kind of resources in the long run, or that there are needlessly allocated resources in the system for long periods of time. This in turn reduc s the capacity and may finally cause the operation to cease if all resources of a certain type have been allocated for one or more tasks which have be n completed a long time ago.

One solution to the problem is offered by fixed-time monitoring which can be used in cases where it is possible to determine a maximum duration for the task to be executed by the resource. The resource is allocated for the maximum period of time, after which the resource releases itself if it has not yet been

5

10

15

20

25

30

35

released. Periodic monitoring has been used for resources allocated for an indefinite period of time or for resources allocated for a very long period of time. It is thereby checked intermittently that all resources in the system have changed tasks. If this has not happened, it is checked whether the main task is still uncompleted throughout the system, on the basis of which the resources are then released or maintained unchanged. One application of this procedure is the virtual memory management, in which the central memory is divided into pages (resources), and the use of different memory pages is monitored during the execution of a program. Unused pages are replaced with new pages from a mass memory whenever required. A disadvantage of periodic monitoring is that it loads the system and is complicated, as the monitoring procedure that checks all allocated resources has to b started intermittently, and if the system has to operate in parallel with the checking routine, a very complicated management algorithm will result as new resources are allocated all the time while old ones are released. In addition, a priority conflict occurs in the fixed-time monitoring of long tasks between the monitoring frequency and the execution if the averag required allocation time is only a fraction of th time required for the entire task so that there occur the needlessly allocated resources within monitoring. For instance, the memory pages to be replaced in the virtual memory management are not released until required, i.e. the central memory may, in principle, be filled up, which reduces the capacity of the system e.g. during the execution of background routines which do not use the virtual memory.

The object of the present invention is to solve the resource management problems by eliminating

WO 94/03855 PCT/F193/00304

3

resource allocations in cases where the resource remains needlessly allocated for an indefinite period of time. To achieve this, the method according to the invention is characterized by

5 allocating a task controller for the management of resources required for a task to be executed;

allocating by the task controller resources required to execute the task;

starting time monitoring in each resource by the controller;

renewing the resource allocations by the controller before the expiry of the respective time monitoring periods, if required by the task; and

releasing by the controller all resources allocated for the task after the completion of the task.

15

20

25

30

35

The task controller according to the invention thus operates so that when it allocates a resource for the execution of a specific task, it also requests the resource to start the time monitoring itself for a period of time which is either equal to the maximum allocation time when this suits the nature of the task, or with a resource to be allocated for an indefinite period of time, the allocation time depends on the distribution of use so that e.g. 90% of all cases (on a statistical basis) are processed within the allocation time. The method according to the invention is suitable for the management of both hardware resources (HW) and software resources (SW, e.g. memory buffers). The method is very reliable in operation as its operability is based on time monitoring, and all error situations can be handled simply by a restart. The method according to the invention is also operative in an environment in which communication between different resources is unreliable. The 5

10

15

20

25

30

35

method supports well the modern modular and objectoriented programming methods.

Other pr ferred embodiments of the method according to the invention are characterized by what is disclosed in the accompanying claims.

In the following the invention will be described by means of examples with reference to the attached drawings, in which

rigures la to lc illustrate the resource management sequence of the method according to the invention in a normal case;

Figure 2 illustrates the renewal of a resource allocation; and

Figures 3a to 3c illustrate various resource allocation release situations.

In Figure 1a, a computer system, such as a central unit 2, i.e. the external environment from the viewpoint of a task to be executed, allocates a controller 1 for the task. The controller may be a hardware or memory area resource capable of controlling other resources in a co-ordinated manner. The controller may be scheduled to release itself spontaneously after the expiry of a fixed time if the external environment 2 does not separately renew it, or it may be releasable by the external environment 2 only.

In Figure 1b, the controller 1 allocates required resources from the computer system; in this specific case, it allocates a read circuit 3 and a memory buffer 4 of a keyboard (not shown) as hardware resources. The task assigned to the controller is thus to read characters from the keyboard to the memory buffer. Moreover, the controller starts a separate time monitoring in the keyboard read circuit and memory buffer 4. The time monitoring period may vary

WO 94/03855 PCT/FI93/00304

5

10

15

20

25

30

35

2

from one resource to another, being e.g. 60 seconds in the read circuit 3 and 120 seconds in the memory buffer 4. As mentioned above, the resources can be allocated on the basis of the maximum time reserved for the task or on the basis of the probable task duration.

After this the time monitoring of the resources does not strain the controller or any other part of the computer system but each resource monitors itself in this respect. Time monitoring can be realized e.g. by a simple time counter program which is attached to the program controlling the operation of each resource or is activated in the program or hardware resource.

In Figure 1c, the system executes a given task by using the allocated resources, and after the task is completed, all resources are released immediately. Communication with the resources takes place via the controller 1. If the controller has been allocated for a fixed period of time, its possible renewal has to take place here, prior to the release of the controller's own time monitoring.

Figure 2 shows a case in which the renewal of a resource is required to complete the task. If the resources allocated in Figure 1b have been allocated for 50 seconds, and the task has not yet been completed, the controller 1 renews the allocation of the read circuit 3 by a renewal request a for another 60 seconds. The buffer 3 thereby acknowledges (arrow b) the further allocation to the controller, or does not accept/does not respond to the renewal request so that the controller can also release itself.

The hand-shaking according to the invention ensures that the resources remain needlessly allocated for no more than the duration of the time monitoring of the particular resource. The resource is released

5

10

15

20

25

30

35

on the basis of the time monitoring only when it is not released by the controller after the completion of the task, i.e. when the resource might otherwise remain allocated for an indefinite period of time; the renewal of allocation is required only seldom, depending on the given use distribution parameters, e.g. in 10% of all cases. Accordingly, the resource management binds very little capacity in the method according to the invention.

The minimizing of the duration of the time monitoring and the minimizing of the number of renewal requests are mutually contradictory objectives depending on the reliability of the system and the available capacity, whereby the required compromise is determined by parametrization, i.e. fixed parameters specific to the central unit, or computed parameters optimized for each task, for instance.

Correspondingly, the allocation of the memory buffer 4 in Figure 2 is renewable, if required, after 110 seconds from the start of the task. After the renewal of the allocation one returns to the situation shown in Figure 1c to wait for the completion of the task.

Figure 3a shows a situation in which a system part (in this specific case the read circuit 3) is damaged and/or incapable of communication. The following renewal request a of the allocation of the task controller 1 thereby fails (the acknowledgement b will not be received), and so the controller 1 releases itself, possibly after having sent an indication c of the failure of the task to its starter (the central unit).

In the situation shown in Figure 3b the fixedtime monitoring at the memory buffer 4 is released, and the memory area is freed. This situation typically WO 94/03855 PCT/FI93/00304

5

10

15

7

results from the hardware failure described in connection with Figure 3a or from the malfunction of the controller. Accordingly, all resources are released when the respective time monitorings are released even though the communication between the resources would be unreliable.

Figure 3c shows a case in which the task controller fails or its allocation for a predetermined time is not renewed so that it is released. Thereafter all other allocated resources are released in accordance with their own time monitoring procedures if there are no renewal requests.

It is obvious to one skilled in the art that the different embodiments of the invention are not limited to the illustrating embodiments described above but they may vary within the scope of the attached claims.

10 (3, 4) required to execut the task; starting time monitoring in each resource by the controller; renewing the resource allocations by the controller before the expiry of the respective time monitoring periods, if required by the task; and 15 releasing by the controller (1) all resources allocated for the task after the completion of the task. 2. Method according to claim 1, characterized in that the task controller (1) is 20 formed as a resource provided with time monitoring. 3. Method according to claim 1 or 2, c h a r in that when the time monitoring acterized period of each resource (1, 3, 4) expires without a renewal, the resource is released spontaneously. 25 4. Method according to claim 1, 2 or 3, c h a racterized in that the time monitoring period of each resource (1, 3, 4) is determined on the basis

of the maximal execution time of the task.

of the probable execution time of the task.

30


5. Method according to claim 1, 2 or 3, c h a r-


acterized in that the time monitoring period


of each resource (1, 3, 4) is determined on the basis


allocating by the task controller (1) resources














FIG. 3c

INTERNATIONAL SEARCH REPORT

International application No. PCT/FI 93/00304

			
A. CLASSIFIC	ATION OF SUBJECT MATTER		
IPC5: G06F	9/46 rnational Patent Classification (IPC) or to both na	tional classification and IPC	
B. FIELDS SE.	ARCHED		
Minimum docume	ntation searched (classification system followed by	classification symbols)	
IPC5: G06F			
	arched other than minimum documentation to the	extent that such documents are included i	n the fields searched
) classes as above		·
Electronic data bas	re consulted during the international search (name	of data base and, where practicable, search	h terms used)
DIALOG 340	347, 350, 351		
	TS CONSIDERED TO BE RELEVANT		
	tion of document, with indication, where app	propriate, of the relevant passages	Relevant to claim No.
			1-5
A US,	A, 4635187 (DONNA M. BARON E 6 January 1987 (06.01.87), co	i AL), olumo 2.	1-5
	line 5 - line 41		
	•		
A EP,	A2, 0094841 (WESTERN ELECTRIC	C COMPANY,	1-5
	<pre>INCORPORATED), 23 November 19 1, abstract</pre>	983 (23.11.83), Tigure	
	1, 455.46		
	 .		
A US.	A, 4435766 (JUDITH G. HABER E	ET AL),	1-5
	6 March 1984 (06.03.84), abst	tract	
	•-		

Further doc	cuments are listed in the continuation of Box	C. X See patent family anne	x.
	ries of cited documents	T later document published after the int date and not in conflict with the appli	ternational filing date or priority ication but cited to understand
to be of partic		the principle or theory underlying the	invention
"E" erlier documen	nt but published on or after the international filing date th may throw doubts on priority claim(s) or which is	"X" document of particular relevance: the considered novel or cannot be considered novel or cannot be considered.	ered to involve an inventive
cited to establish special reason	ap the happication date of snother citation or other	step when the document is taken alon "Y" document of particular relevance: the	claimed invention cannot be
O' document refer	rring to an oral disclosure, use, exhibition or other	considered to involve an inventive sta combined with one or more other au	p when the document is th documents, such combination
"P" document publ	lished prior to the international filing date but later than	being obvious to a person skilled in the document member of the same patent	he art
Date of the actu	al completion of the international search	Date of mailing of the international	
		0.0 44 4000	
28 October	1993	0 3 -11- 1993	
	ng address of the ISA/	Authorized officer	
Swedish Pater Box 5055, S-10	nt Office D2 42 STOCKHOLM	Katarina Fredriksson	
	+ 46 8 666 02 86	Telephone No. +46 8 782 25 00	

Form PCT/ISA/210 (second sheet) (July 1992)

Information on patent family members

01/10/93 PCT/FI 93/00304

. Patent of cited in se	document arch report	Publication date		it family mber(s)	Publication date
S-A-	4635187	06/01/87	CA-A- DE-A- EP-A,B- SE-T3-	1218752 3468556 0165934 0165934	03/03/87 11/02/88 02/01/86
P-A2-	0094841	23/11/83	EP-A-	0110950	20/06/84
JS-A-	4435766	06/03/84	JP-C- JP-B- JP-A-	1605016 2030057 57207957	13/05/91 04/07/90 20/12/82

Form PCT/ISA/210 (patent family annex) (July 1992)